

ELEKTRISK LUFTGARDIN

Newly designed to maximize performance

High Air volume upgraded 145% compared to conventional model (in the case of FY-3009U1).

Comprehensive product line up

1,5m wide model added in the line up.

Easier installation & maintenance

Simple structure for easy installation & maintenance.



| ELEKTRISK LUFTGARDIN | | Enkeltfaset | | |
|------------------------|---------------------|-------------|-----------|-----------|
| | | kW | kW | kW |
| Reference | | FY-3015U1 | FY-3012U1 | FY-3009U1 |
| Width | mm | 1500 | 1200 | 900 |
| Power supply (Voltage) | V | 220 | 220 | 220 |
| Air flow (Hi) | m ³ /min | 2000 | 1400 | 1100 |
| Air flow (Lo) | m ³ /min | 1800 | 1270 | 920 |
| Power consumption (Hi) | W | 131 | 94 | 76 |
| Power consumption (Lo) | W | 110 | 85 | 70 |
| Current (Hi) | A | 0,59 | 0,43 | 0,35 |
| Current (Lo) | A | 0,50 | 0,40 | 0,32 |
| Air speed (Hi) | m/s | 10,50 | 9,50 | 10,50 |
| Air speed (Lo) | m/s | 9,50 | 8,00 | 8,50 |
| Dimension (Height) | mm | 1500 | 1200 | 900 |
| Dimension (Width) | mm | 231,5 | 231,5 | 231,5 |
| Dimension (Depth) | mm | 212 | 212 | 212 |
| Net weight | kg | 18,0 | 14,5 | 12,0 |
| Sound pressure (Hi) | dB(A) | 51,5 | 48,5 | 48,5 |
| Sound pressure (Lo) | dB(A) | 48,0 | 44,5 | 45,0 |

Supplerende produkter